



BAX-P501-C236

ATX Barebone System with Intel® C236 Chipset



- > 4 x 288-pin DDR4 2133MHz U-DIMM socket, supports up to 64GB (ECC support by CPU)
- > 1 x VGA, 1 x DP, 1 x HDMI, Triple Display
- > 1 x PCIe x 16, 4 x PCI (Support 5V), 1 x PCIe x 4, 1 x PCIe x 1
- > 1 x Full Size Mini PCIe, 1 x M.2 Key A 2230
- > 6 x USB 3.0, 2 x USB 2.0
- > 6 x COM, 1 x PS2 KB & Mouse, 1 x Line-out
- > 2 x 5.25" Drive Bays, 1 x 3.5" Drive Bays
- > 1 x Standard PS2 ATX 350W Power Supply
- > 7 x Full Height Expansion Slot

+ Spec

System	
Processor	Intel® 6th Generation Xeon®, Core™ i7/i5/i3, Pentium® and Celeron® Processors (Max. TDP at 95W)
System Chipset	Intel® C236 Chipset
System Memory	4 x 288-pin DDR4 2133MHz U-DIMM socket, supports up to 64GB (ECC support by CPU)
H/W Status Monitor	Monitoring System Temperature and Voltage with Auto Throttling Control
Board	EAX-C236P
Expansion	
Expansion	7 x Full Height Expansion Slot
Storage	
Storage	2 x 5.25" Drive Bays 1 x 3.5" Drive Bays
I/O	
USB	2 x USB 2.0 6 x USB 3.0
COM Port	6 x RS-232
MIO	1 x PS/2 Keyboard & Mouse
Display	
Chipset	Intel® 6th Generation CPU integrated
Resolution	VGA: 2048 x 1536 @ 60Hz HDMI: 3840 x 2160 @ 30 Hz, 2560 x 1600 @ 60 Hz DP: 4096 x 2304 @ 60Hz
Multiple Display Interface	Triple Display VGA HDMI DP
Audio	
Chipset	Realtek ALC892
Audio Interface	Mic-In, Line-In and Line-Out
Ethernet	
Chipset	1 x Intel® I219-LM Gigabit Ethernet PHY 1 x Intel® I211-AT PCIe Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Dimensions(W x L x D)	450 x 196 x 330 mm
Operating Temp	(w/HDD), ambient w/ air flow 0°C ~ 40°C (32°F ~ 104°F)
Storage Temp	-20°C ~ 75°C (-4°F ~ 167°F)
Construction	Metal
Power Requirement	
Power Mode	ATX
Adapter	Standard PS2 ATX 350W Power Supply

+ Ordering

BAX-P501-C236-A1R
ATX Barebone System with Intel® C236 Chipset

