



REV	DESCRIPTION	DATE
-----	-------------	------

△ RDCM-107002 林淑禎 2018/01/24

- NOTE :
1. MAXIMUM ELECTRIC CURRENT : $\frac{\text{A.W.G.} \begin{matrix} 16 \\ 14 \end{matrix}}{\text{AMP.} \begin{matrix} 10 \\ 15 \end{matrix}}$
 2. MAXIMUM ELECTRICAL RATING : 105°C 600 VOLTS MAX.
 3. INSULATION MATERIAL : NYLON
 4. INSULATION COLOR : BLUE
 5. TERMINAL MATERIAL : BRASS
 6. WIRE RANGE : 16-14 A.W.G. (1.5-2.5 mm²)
 7. NEMA TAB : 0.032 inch * 0.250 inch (0.8 mm * 6.35 mm)
 8. DOUBLE CRIMP : WITH SHORT COPPER SLEEVE ON BARREL
 9. TERMINAL SURFACE TREATMENT : TIN PLATED
 10. TERMINAL THICKNESS : 0.40 mm

Tolerance Unless Otherwise Specified	
0 > 6 mm ±0.20	ANGLE
6 > 18 mm ±0.30	0° REF ±
18 > 30 mm ±0.40	° ±
30 > 75 mm ±0.50	° ±

NAME	PLASTIC STRIP ON REEL TYPE (NYLON-INSULATED PS SERIES)			UNIT	mm	<input type="checkbox"/>	<input type="checkbox"/>
PART NO.	FDNYDX2-250-PS	MATERIAL	-----	APPROVE			
NUMBER	KA-94206-C	SCALE	SHEET PAGE	CHECKED			
DATE	2007/02/12	2/1	1-1	10F1	DRAWN	張馨尹	

KST. K.S. TERMINALS INC.