

SPECIFICATION FOR APPROVAL

COMMODITY	MULTILAYER CHIP INDUCTOR	SPEC NO.	SP-060927165
ITEM	JCI 3216-1R0K Green	版本：A	表單編號：TRR-002

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	3.2	±0.2
	B	1.6	±0.2
	C	1.1	±0.2
	D	0.5	±0.3
	E		
	F		
	G		
	H		
	I		
	J		

(2) ELECTRICAL CHARACTERISTIC	TEST INSTRUMENTS.
INDUCTANCE	1.0 ± 10% μH
Q	45 (min)
TEST FREQUENCY	10 MHz
TEST VOLT	0.25 V
SRF	75 (min) MHz
RDC	0.4 (max) Ω
IDC	100 (max) mA

AGILENT 4294A Precision Impedance Analyzer.
 AGILENT 4285A Precision L.C.R. Meter.
 HP-4286A RF L.C.R. Meter.
 ZENTECH 3302 Automatic Components Analyzer.
 ZENTECH 101 L.C.R. Meter.
 WAYNE KERR 6420 Precision Impedance Analyzer.
 ZENTECH 1320 BIAS CURRENT.
 ZENTECH 502AC Resistance Merter.
 ADEX AX-1155B DC Low Ohm Meter.

REMARK :

PURCHASER CONFIRMED	APPROVED	CHECKED	DRAWN