

MTX-ROUTER-HELIOS Lite 3G

3G/2G compact industrial IoT router

The MTX-Router-Helios Lite 3G is the new industrial router developed for industrial applications. The router has a very compact design with a very rugged enclosure and accessories to be mount in a DIN rail or wall mount. This is the best choice if you are looking for a simple but industrial GPRS or 3G router to connect your device or network into the cellular network.

The MTX-Router-Helios Lite can be used in many different IOT applications like kiosk, telemetry, remote sensing, smart grid, security, industrial automation, etc...




MAIN FEATURES




3G connectivity



WiFi



Ethernet



RS232/
RS485




DIN rail



DHCP



Firewall



Serial tunnelling



DynDNS



Programmable
autoreset



VLAN



Remote
management

-  DC: 5-35 Vdc
-  Temperature range: -35° to +75°C
-  Dimensions: 100x97x25mm
-  Weight: <320gr

Preliminary Datasheet. Subject to changes | 2017/09
MTX © by MATRIX ELECTRONICA S.L.U.
SUPPORT: iotsupport@mtx2m.com
SALES: info@mtx2m.com
mtx2m.com



HARDWARE FEATURES

	MTX-ROUTER-HELIOS Lite 3G	MTX-ROUTER-HELIOS Lite 2G
	EUROPE: UMTS/HSPA+ 850/1900/2100MHz US*: GSM850/900/1800/1900 MHz	WORLDWIDE: Quad-Band GSM; bands: 850, 900, 1800 & 1900 MHz
	HSPA+ (3GPP release 7): DL 84Mbps, UL 22Mbps; MIMO HSPA (3GPP release 6, 7): DL 7.2Mbps, UL 5.7Mbps; HSDPA Cat.8/HSUPA Cat.6 data rates	
	GPRS Class 12; mobile station class B; PBCCH support; coding schemes CS 1-4	GPRS Class 12; mobile station class B; PBCCH support; coding schemes CS 1-4

*Optional, under request

Interfaces

-  3G/2G connectivity
-  1x Ethernet 10/100 BaseT
-  1x RS232 (4-wire) or 1x RS485/232 (2-wire)
-  WiFi 802.11 b/g/n (optional)
-  Operating LEDs
-  SIM card interface 1.8V/3V
-  Console port connector
-  DIN rail

Connectors

-  1x RJ45: Ethernet 10/100 BaseT
-  1x RJ45: console port connector, RS232/485
-  SIM card
-  1x SMA F antenna connector: 3G
-  1x SMA F RF antenna connector: WiFi
-  DC power jack: power input

Packing List Included

-  Power adapter
-  DIN rail and wallmount kits
-  Console port cable: RJ45 to DB9 H
-  Ethernet cable
-  WiFi antennas
-  LTE antennas

SOFTWARE FEATURES

-  DHCP server
-  NAT/IP firewall
-  QoS
-  Serial tunnelling
-  Multiple DDNS provider supported
-  Schedule reboot, schedule online and off-line
-  VLAN management
-  Remote management (web, SSH, Telnet)
-  Remote firmware upgrade

ORDERING INFORMATION

MTX-Router-Helios Lite 3G	502300037
MTX-Router-Helios Lite GPRS	502300038
MTX-Router-Helios Lite 3G WiFi	502300039