



REV	ECN NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	17.04.29

NOTES:

- Rating: <UL> 300V/16A  
<IEC> 320V/20A
  - Poles: 02-24P
  - Insulation Withstands Voltage: AC2000V/1 Min
  - Screw Torque Value: 0.4Nm
  - Insulation Resistance: 500M  $\Omega$  at DC500V
  - Using Temperature Range: -40°C/+115°C
  - Suitable Electric Wire: 12-28AWG(UL) 25mm<sup>2</sup>(IEC)
  - Strip length: 7-8mm
  - 9 ROHS compliance
10. With "★" is important dimension

How to order **ULO-1B23 - 2KA/5.0 - XXP - Y 0 0 0A**

Certificate Factory poles color: Customer requirements  
 Series NO. Code  
 1: Grey  
 2: Blue  
 3: Black  
 4: Green  
 5: Orange  
 6: Red  
 7: transparent  
 8: Yellow  
 9: White

5	SCREW	S000000170	N	STEEL	M2.5/Zn Plated
4	Clamp	1030B0V10	N	Phosphor Bronze	Trm Plated
3	BLDCK	X000000170	N	Brass	Ni Plated
2	Cover	1030C0YXXA	1	PA66	UL94V-0
1	Housing	1030A0YXXA	1	PA66	UL94V-0

ITEM	NAME OF PART	NO OF PART	Q'TY	MATERIAL	NOTE
DWG	ZCP	17.04.29	UNITS	MM	SHEET/OF 1/1
CHK	DATE		SCALE	1 : 1	A4
APP	DATE		NAME	<b>ULO-1B23-2KA/5.0-XXP-Y000A</b>	



NINGBO ULO ELECTRONICS CO., LTD.  
 宁波微路电子有限公司  
 DWGNO: ULO1B23Y000A

Total Pitch Tolerances		Nominal dimension range	
In mm		In mm	
0	over	0	over
30	to	30	to
53	to	53	to
70	to	70	to
90	to	90	to
115	to	115	to
150	to	150	to
200	to	200	to
250	to	250	to
300	to	300	to
320	to	320	to
330	to	330	to
350	to	350	to
400	to	400	to
450	to	450	to
500	to	500	to
550	to	550	to
600	to	600	to
650	to	650	to
700	to	700	to
750	to	750	to
800	to	800	to
850	to	850	to
900	to	900	to
950	to	950	to
1000	to	1000	to