



REV	E.C.N NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	16.12.28

- NOTES:
- Rating: 300V/16A
<IEC> 320V/20A
 - Poles: 02-24P
 - Insulation Withstands Voltage: AC2000V/1 Min
 - Screw Torque Value: 0.4Nm
 - Insulation Resistance: 500MΩ at DC500V
 - Using Temperature Range: -40°C/+115°C
 - Suitable Electric Wire: 12-28AWG(UL) 2.5mm²(IEC)
 - Strip length: 7-8mm
 - ROHS compliance
 - With "★" is important dimension

How to order
ULO-TB29 - 2KA/5.08 - XXP - Y 0 0 0A
 Certificate Factory poles color: Customer
 Series NO. Code requirements
 1: Grey
 2: Blue
 3: Black
 4: Green
 5: Orange
 6: Red
 7: transparent
 8: Yellow
 9: White

5	SCREW	S000000190	N	STEEL	M2.5/Zn Plated
4	Clamp	1030B0010	N	Phosphor Bronze	Tin Plated
3	BLOCK	X000000170	N	Brass	Ni Plated
2	Cover	1031C0YXXA	1	PA66	UL94V-0
1	Housing	1031A0YXXA	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCP	DATE	16.12.28	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
	NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司			NAME	ULO-TB29-2KA/5.08-XXP-Y000A
				DWGNO.	ULOTB29Y000A

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	-	//		
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	all	over 0	over 100	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5		