



REV	EC.N NO.	CONTENT	CHK	DATE
V0.0		初版成	ZCP	

NOTES:

- Rating: 150V/6A
<IEC> 130V/8A
 - Poles: 02-24P
 - Insulation Withstands Voltage: AC2000V/1 Min
 - Contact resistance: 20m Ω
 - Screw Torque Value: 0.2Nm
 - Insulation Resistance: 500M Ω at DC500V
 - Wire range: 0.5-1.0mm² (IEC), 18-26AWG(UL);
 - Using Temperature Range: -40°C/+115°C
 - RoHS Compliance.
 - 10 With "★" is important dimension
- How to order
UL0-TB17 - 308/2.54 - XXP - Y 0 0 0A
- Certificate Factory poles color: Customer requirements
 Series NO. Code
- 1: Grey
 - 2: Blue
 - 3: Black
 - 4: Green
 - 5: Orange
 - 6: Red
 - 7: transparent
 - 8: Yellow
 - 9: White

Total Pitch Tolerances		Nominal dimension range		T		≠		—		//					
in mm		in mm													
0	30	53	70	90	115	150	200	250	0	over	0				
to	to	to	to	to	to	to	to	to	to	all	to				
30	53	70	90	115	150	200	250	320	10	100	150				
to	to	to	to	to	to	to	to	to	to	to	to				
+18	+0.20	+0.25	+0.3	+0.35	+0.44	+0.55	+0.70	+0.80	+0.90	0.2	0.3	0.3	0.2	0.3	0.5

4	Screw	3160000025	N	Steel	Zn Plated/M1.6
3	Solder Pin	3110000023	N	Brass	Sn Plated
2	Gage	3090000011	N	Brass	Ni Plated
1	Housing	4050000471	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	DATE	18.10.16	UNITS	MM	SHEET/OF 1/1
CHK.	DATE		SCALE	1:1	A4
APP.	DATE		NAME	UL0-TB17-308/2.54-XXP-Y000A	
NINGBO UL0 ELECTRONICS CO., LTD. 宁波欧路电子有限公司			DWGNO.	UL0TB17Y010A	