

12" Android Network Digital Signage

Right Message At Right Time



Digital Signage is the remote-controlled distribution and playback of digital content (TV programs, advertising, menus, and every sort of information) on networks of displays. These displays can range from digital billboards to much smaller screens, either at a single location or across multiple sites. It's all about targeting the audience with relevant information. Digital signage enables users to display their messages more dynamically and targeted.

RCSTARS has demonstrated a Digital Signage application on android platform. The application provides the features of updating the content from remote web browser, playback of video content, image, HTML web pages and scrolling text messages.

Key Features:

- Android 4.4 operating system
- Rockchip RK3188 Quad Core CPU
- 1/2GB DDR3 + 8/16GB Flash
- 802.11 b/g/n internal Wifi
- 3G/WIFI/WLAN Network connection
- Remote Management Software
- Portrait & Landscape display mode
- 1080P Display output
- Capacitive touch/IR touch screen optional

Designed for:


- POS
- Hotel
- Self-service Terminal
- Public Information Display
- Hospitality
- In-vehicles And Transportation



12" Android Network Digital Signage







Specifications

Panel Model Max Resolution Aspect Ratio Pixel Pitch Viewing Angle Contrast Ratio Brightness Response Time Display Area (mm) Panel Size(mm) Screen Weight Lamp Type	12.1inch TFT LED 1280x800(WXGA) 16:10 0.204x0.204 80/80/65/80 800:1 400cd/m ² 35ms 261.12x163.2mm 278x184x8.6mm 550g WLED
CPU GPU RAM ROM OS	Quad-core ARM Cortex-A9,1.6GHz ARM Mali-400MP4 1/2GB DDR3 8/16 GB Flash Android 4.4
USB 2.0 HDMI (Output) SD Rj45 3G SIM (Optional)	X2 X1 X1 X1 X1 X1
LAN WiFi 3G (Optional)	RJ45 Port, 10/100M Ethernet Built-in WiFi 802.11B/G/N WCDMA
Video Image Audio Scrolling Text	H.264, MKV, WMV9, MPEG 1/2/4, HD Divx, Xvid, RM/RMVB; BMP/PNG/GIF/JPEG MP3,WMA,WAV,EAAC+, MP2 dec, Vorbis (Ogg), AC3, FLAC, APE, BSAC txt
	Max Resolution Aspect Ratio Pixel Pitch Viewing Angle Contrast Ratio Brightness Response Time Display Area (mm) Panel Size(mm) Screen Weight Lamp Type CPU GPU RAM ROM OS USB 2.0 HDMI (Output) SD SG SIM (Optional) LAN WiFi 3G (Optional) Video Image Audio

HDMIDISPLAY	Output Mode	HDMI 480P
I DIVI DISFLAT	Output Mode	HDMI 480P
		HDMI 720P 50Hz
		HDMI 720P 60Hz
		HDMI 1080I 50Hz
		HDMI 1080I 60Hz
		HDMI 1080P 24Hz
		HDMI 1080P 50Hz
		HDMI 1080P 60Hz
ON-SCREEN DISPLAY LANGUAGES		English, French, German, Italian, Polish Russian, Simplified Chinese, Spanish, Turkish, Arabic, Japanese, Traditional Chinese etc.
DISPLAY MODE		Portrait & Landscape
тоисн		P-CAP Touch / infrared Touch (optional)
POWER	Mains Power	DC 12V, 50-60 Hz
	Consumption	15 W
SOUND	Built-in Speakers	2 x 5W
DIMENSION & WEIGHT	Machine Size	301x213.5x48mm
	Machine Weight	1.8KG
	Carton Size	385x95x297mm
	Carton Weight	2.5KG
	Carton Size	500x400x320mm (5PCS)
	Carton Weight	15.2KG
OTHER	Regulatory Approvals	CE, FCC, ROHS
	Warranty	1 year warranty
ACCESSORIES	Included	Remote Control, Power supply,
		User manual, Keys, Screws

Specifications And Availability Are Subject To Change Without Notice. Trademarks Are The Property Of Their Respective Owners. Copyright © 2017 Rcstars Technology. All Rights Reserved.