

32" 4K UHD Monitor

M320TF-SDI

Update your OR with the newest display technologies



Product Features

- 32" Display with UHD 4K (3840 x 2160) native resolution
- Thin and compact design with impact resistant screen
- 3D Look Up Table (LUT) providing rich and deep depth perception
- Fanless and ventless design, easy-to-clean
- Compatible with existing imaging systems
- Antimicrobial surface coating
- 4K Signal Input HDMI/DP/12G-SDI




Solving challenges in the hospital with the right technology. Technology has long played an imperative role in streamlining hospital operations and improving patient care. Healthcare personnel need to be assured that each image, or streaming images, being viewed are an accurate depiction of the tissue and bone being studied.

Designed for surgical suites demanding reliability and the latest technology.

Zoom in by Region	Fanless	Ultra HD	In-Plane Switch	Image Adjust by Region	Capacitive touch keys	DICOM GSDF (Optional)	HDMI 2.0
3D Look Up Table	Signature True Flat With Slim design	Wide Viewing ANGLE 178°	Built-in Speaker	World Wide Service and Support	Calibration software tool (Optional)	Display Port 1.2	Ambient light sensor

12G-SDI
12G-SDI

Mechanical Drawing



Product Specifications

Screen Technology	LED Backlight Technology, TFT Active-matrix, Widescreen, IPS Technology
Viewable Size	32" diagonal
Active Area	708.48 (H) x 398.52 (V) mm
Native Resolution	3840 x 2160 (UHD 4K)
Pixel Pitch	184.5 (H) x 184.5(V) um
Aspect Ratio	16:9
Response Time	12ms (Gray to Gray)
Light Intensity	350 cd/m ² 700 cd/m ² (Optional)
Contrast Ratio	1000:1 (typ)
View Angle	89/89/89/89
Max Colors	1.07B
Touch	Projected Capacitive Touch, USB interface AR Glass (Optional)
Color Profiles	Support 3D LUT profile 6 x general user color schemes DICOM GSDF (Optional)
Product Features	Ambient light sensor IR Control Internal Backlight sensor (Optional for 700 cd/m ²)
Power Specifications	12V DC in, 110-240V AC to DC Adapter
User Controls and Activity	Capacitive OSD : Power On/Off, On Screen Display Menu, Brightness Control (-/+)

Input Signal	<ul style="list-style-type: none"> 12G-SDI HDMI 2.0 USB for Touch RS232 for Remote Control 	<ul style="list-style-type: none"> HDMI 1.4 DP 1.2
Output Signal	<ul style="list-style-type: none"> 12G SDI (Loop Through) 	
Product Dimensions	777.58 x 477.62 x 48 mm (30.6 x 18.8 x 1.8 in)	
Mounting	VESA mounting 100 x 100mm VESA mounting 200 x 100mm VESA mounting 300 x 100mm	
Product Weight	11 Kg (24.2 lbs)	
Housing	Antimicrobial Surface Coating	
Operating Temperature	0 deg.C to 35 deg.C, Humidity up to 95%	
Storage Temperature	-20 deg.C to 60 deg.C, Humidity up to 95%	
IP Rating	Protection: front IP65 - rear IP22	
Type Approval, Testing and Certificates	<ul style="list-style-type: none"> CE FCC 	

