

### HEIDI

Ø21.6 mm easily sealable TIR-lenses for up to 3535 size LED packages

TIR-lens with multiple beam patterns designed to be easily protected against the environment by conformal coatings. Available with or without two-sided adhesive tape.




### PRODUCTS:

#### C13738\_HEIDI-M-NP


**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.60 mm**  
~25° medium beam. Version without location pins.

#### CA12536\_HEIDI-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.70 mm**  
~25° medium beam


#### CA11265\_HEIDI-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.90 mm**  
~25° medium beam

### PRODUCTS:

#### CA14197\_HEIDI-REC-90




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 12.85 mm**

~35° + 55° rectangular beam

#### CA12443\_HEIDI-SS




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 11.70 mm**

~15° smooth spot beam optimized  
for LUXEON Rebel ES

#### CA12079\_HEIDI-W2




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 12.00 mm**

~45° wide beam

#### CA12815\_HEIDI-O-90




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 11.70 mm**

~13° x 45° oval beam optimized for  
Luxeon Rebel. Variant with beam  
direction rotated 90°.

#### CA11268\_HEIDI-W




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 11.70 mm**

~32° wide beam

#### CA12537\_HEIDI-RS




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 11.70 mm**

~8° spot beam


### PRODUCTS:

#### CA11266\_HEIDI-O




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.90 mm**  
~50° x 11° oval beam

#### CA12530\_HEIDI-D




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.70 mm**  
~10° diffused spot beam optimized  
for LUXEON Rebel ES

#### CA11264\_HEIDI-D




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.90 mm**  
~10° diffused spot beam

#### CA14000\_HEIDI-M-NP




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.60 mm**  
~25° medium beam. Version without  
location pins.

#### CA12242\_HEIDI-SS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.70 mm**  
~15° smooth spot beam


#### CA12949\_HEIDI-O



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 11.70 mm**  
~50° x 11° oval beam

### PRODUCTS:

#### CA11663\_HEIDI-RS




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 11.70 mm**

~8° spot beam

#### CA12538\_HEIDI-W




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 11.70 mm**

~30° wide beam optimized for  
LUXEON Rebel ES

#### CA11267\_HEIDI-O-90



**Dimensions: 21.6 mm x 21.6 mm**

**Height: 12.10 mm**

~13° x 45° oval beam optimized for  
Cree XP-G and XP-E. Variant with  
beam direction rotated 90°.

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)