



NOTES1:

UL Standard

1. Rating voltage/current: 300V/16A
2. withstanding voltage: AC1600V/1Min

IEC Standard

1. Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0KV
Rate Voltage(V)	320V
Rate Current(A)	20A

NOTES2:

1. Housing: PA66(UL94V-0)
2. Solder Pin: Brass(Sn Plated)

NOTES3:

1. Pitch: 5.08mm Poles: 02~24P
2. Operating temperature: -40℃~+105℃
4. RoHS Compliance

How to order

ULO-TB27 - 2VC/5.08 - XXP - Y 0 0 0A

Certificate Factory poles Customer
Series NO. Code requirements

color:

- | | |
|----------|---------------|
| 1:Grey | 6:Red |
| 2:Blue | 7:transparent |
| 3:Black | 8:Yellow |
| 4:Green | 9:White |
| 5:Orange | |

Total Pitch Tolerances in mm										Nominal dimension range in mm										PCB Layout			≡		—		//																											
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	0	over	0	over	0	over	0	over	0	over	10	all	10	100	150																				
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to																																			
0	30	53	70	90	115	150	200	250	320	0	30	53	70	90	115	150	200	250	320	0	10	0	100	0	100	0	100	0	150	0.18	0.20	0.25	0.3	0.35	0.44	0.55	0.70	0.75	0.80	0.25	0.30	0.35	0.44	0.55	0.70	0.80	0.90	0.2	0.3	0.3	0.3	0.2	0.3	0.5

ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	Z J L	DATE	20.11.28	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
				NAME	ULO-TB27-2VC/5.08-XXP-4000A
				DWGNO.	ULOTB27Y000A