



NOTES1:
UL Standard

Use group	B	C	D
Rated Current	15A	-	10A
Rated Voltage	300V	-	300V

IEC Standard

Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0KV
Rate Voltage(V)	320V
Rate Current(A)	20A

NOTES2:
1.Housing: PA66(UL94V-0)
2.Solder Pin: Red copper(Sn Plated)

NOTES3:
1.Pitch: 5.08mm Poles: 02~24P
2.Operating temperature: -40℃~+105℃
4:RoHS Compliance

How to order
ULO-TB27 - 2VC/5.08 - XXP - Y 0.00A
Certificate Factory poles
Series NO. Code Customer requirements

- color:
- 1:Grey
 - 2:Blue
 - 3:Black
 - 4:Green
 - 5:Orange
 - 6:Red
 - 7:transparent
 - 8:Yellow
 - 9:white

Total Pitch Tolerances

In mm		Nominal dimension range																						
over	to	0	30	53	70	90	115	150	200	250	300	320	360	400	450	500	550	600	650	700	750	800	850	900
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5	0.5

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	ZJL	DATE	20.11.28	MM	SHEET/OF
CHK	DATE	SCALE	1:1	A4	1/1
APP	DATE	NAME	ULO-TB27-2VC/5.08-XXP-4000A		



NINGBO ULO ELECTRONICS CO.,LTD
宁波欧路电子有限公司