

A

21070-B

210x210x70mm(8.27"x8.27"x2.76")



HOUSING	Aluminum Die Casting, Painted Blue/Black
IMPELLER	Thermoplastic PBT, UL94V-0, Blue/Black
BEARING	Ball
OPERATING TEMPERATURE	-10°C to + 70°C
INSULATION	Class A
OPERATING VOLTAGE RANGE	200 VAC to 240 VAC for 220V Type
DIELECTRIC STRENGTH	5mA Max. at 1500 VAC for 1 second
INSULATION RESISTANCE	10M Ω min. @500 VDC
MOTOR TYPE	AC Induction Capacitor Motor
SAFETY	Thermally Protected
TERMINATION	Lead Wire
WEIGHT	1.7 kg
ROHS COMPLIANCE	Yes
IP LEVEL	IP21(Special IP Rating On Request)


210

 mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
A21070V2HBL-B	220	0.2/0.25	45/55	2550/3000	0.37/0.28	9.4/7.0	379/402	10.73/11.38	70/75

DIMENSION



AIR PERFORMANCE

