



KL-224

KL-225

Typ Type	Artikel-Nr. Part no.	Abmessung Dimension		Thermischer Widerstand Thermal resistance (K/W)
		L	L1	
KL-205/25,4/sw	2050808	25,4		11,5
KL-205/25,4/sw/v	2050801	25,4		11,5
KL-205/25,4/sw/v/i	2050806	25,4		11,5
KL-205/38,1/sw	2051808	38,1	25,4	9
KL-205/38,1/sw/v	2051801	38,1	25,4	9
KL-205/38,1/sw/v/i	2051806	38,1	25,4	9
KL-205/50,8/sw	2052808	50,8	25,4	7
KL-205/50,8/sw/v	2052801	50,8	25,4	7
KL-205/50,8/sw/v/i	2052806	50,8	25,4	7
KL-207/25,4/sw	2070808	25,4		10,5
KL-207/25,4/sw/v	2070801	25,4		10,5
KL-207/25,4/sw/v/i	2070806	25,4		10,5
KL-207/38,1/sw	2071808	38,1	25,4	8
KL-207/38,1/sw/v	2071801	38,1	25,4	8
KL-207/38,1/sw/v/i	2071806	38,1	25,4	8
KL-207/50,8,sw	2072808	50,8	25,4	6
KL-207/50,8/sw/v	2072801	50,8	25,4	6
KL-207/50,8/sw/v/i	2072806	50,8	25,4	6

sw: Schwarz eloxiert/Black anodized
 i: Mit Isolierringen/With insulation rings
 v: Mit lötbaren Messinghülsen/With solderable brass pins

Typ Type	Artikel-Nr. Part no.	Abmessung Dimension		Thermischer Widerstand Thermal resistance (K/W)
		L	L1	
KL-224/25,4/sw	2240808	25,4		12
KL-224/25,4/sw/v	2240801	25,4		12
KL-224/25,4/sw/v/i	2240806	25,4		12
KL-224/38,1/sw	2241808	38,1	25,4	9,5
KL-224/38,1/sw/v	2241801	38,1	25,4	9,5
KL-224/38,1/sw/v/i	2241806	38,1	25,4	9,5
KL-224/50,8/sw	2242808	50,8	25,4	7,5
KL-224/50,8/sw/v	2242801	50,8	25,4	7,5
KL-224/50,8/sw/v/i	2242806	50,8	25,4	7,5
KL-225/25,4/sw	2250808	25,4		9
KL-225/25,4/sw/v	2250801	25,4		9
KL-225/25,4/sw/v/i	2250806	25,4		9
KL-225/38,1/sw	2251808	38,1	25,4	7
KL-225/38,1/sw/v	2251801	38,1	25,4	7
KL-225/38,1/sw/v/i	2251806	38,1	25,4	7
KL-225/50,8/sw	2252808	50,8	25,4	5,5
KL-225/50,8/sw/v	2252801	50,8	25,4	5,5
KL-225/50,8/sw/v/i	2252806	50,8	25,4	5,5

sw: Schwarz eloxiert/Black anodized
 i: Mit Isolierringen/With insulation rings
 v: Mit lötbaren Messinghülsen/With solderable brass pins