



CAXA0

10.1" Semi-Rugged Tablet with Intel® Celeron® Processor N3350

- > Semi-rugged design with Intel Celeron N3350
- > MIL-STD-810G & IP65 certified, 4-feet drop resistance
- > 10.1" TFT color LCD 1280 x 800 HD
- > Corning Gorilla Glass, 10 point projected capacitive multi-touch panel
- > High mobility with multiple connectivity including WLAN, Bluetooth, NFC
- > Light Design, Weight only 1Kg with Battery
- > G-sensor, light sensor, 2M/8M Camera
- > Option SCR, 1D/2D Barcode scanner

Spec

System Information	
Processor	Intel® Celeron® Processor N3350 (2M Cache, up to 2.4 GHz)
System Memory	Onboard LPDDR4 4GB
Storage	
Solid State Drive	M.2 64GB Solid State Drive
Panel	
LCD Size	10.1"
Display Type	WXGA
Resolution	1280x800
Luminance	300 cd/m ²
Touch Type	10 Points Projective Capacitive
I/O	
USB Port	2 x USB 3.0 Type A
HDMI	1 x HDMI Output
Other	1 x Audio Jack 1 x Micro SD 1 x DC Jack
System Control	
LED Indicator	1 x Power
Control Buttons	1 x Power Button 1 x Barcode Scanner Trigger
Data Collection	
Camera	2MP Front Camera 8MP Rear Camera With Auto Focus
NFC	ISO/IEC 14443 A/B, 15693/18092, NFCIP-1, NFCIP-2, Support MIFARE and Felica
Barcode Scanner	1D/2D Barcode Scanner (Optional)
Smart Card Reader	Half-Slot, Reads ISO 7816-1, 2, 3 & 4, T=0 & T=1; 5V Smart Card Reader (Optional)
Wireless Communication	
WLAN	802.11 a/b/g/n/ac
Bluetooth	Bluetooth 5.0
Certifications	
Certification Information	CE, FCC, VCCI, CCC, BSMI EN60601-1, EN60601-1-2
Power Requirement	
DC Input	+19V
DC Input Connector	DC Jack
Adapter	Input: 100~240Vac/50~60 Hz Output: 65W Adaptor (19V@3.15A Adaptor)
Battery Operating Time	6 Hours
Battery	28.44W Li-ion Battery
Mechanical & Environmental	
Operating Temperature	0°C to 40°C (32°F to 104°F) 0°C to 30°C (32°F to 86°F) without dock or wall mount [EN60601] 0°C to 40°C (32°F to 104°F) with dock or wall mount [EN60601]
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Operating Humidity	15%~95% Relative Humidity, Non-Condensing
Weight	1Kg
Vibration Test	MIL-STD-810G Method 514.6 Procedure 1
Shock Test	MIL-STD-810G Method 516.6 Procedure 1



IP Rating	IP65
Dimension	281 x 193.3 x 19.95mm
Storage Humidity	5%~90% Relative Humidity, Non-Condensing
Drop	4-Feet Drop on Concrete Floor, MIL-STD-810G 516.6 Procedure IV
Construction	Rubber + Plastic
Software Support	
OS Information	Windows 10 IoT 64bit Android 8.1 without NFC,Barcode scanner, Smart card reader
In-Box Accessory	
Accessory	+19V 65W Power Adaptor
Component	
Microphone	Front Microphone