

# Shenzhen Top Power Co., Ltd.

Add:3/F.,Bldg.B5,Junfeng Industrial Park,Yonghe Road,Heping,Fuyong,Shenzhen

Tel:+86-755-23359172 29919580 Fax:+86-755-29919580

<http://www.sz-toppower.com>

Contact:Henry Email:henry@sz-toppower.com Skype:toppower.henry

## 36w eu catalogue

Item	Description	Photo
1	<p>Model Name: <b>TPS-0505000EU(5V 5A), TPS-0604000EU(6V 4A), TPS-0903000EU(9V 3A), TPS-1203000EU(12V 3A), TPS-1502000EU(15V 2A), TPS-1802000EU(18V 2A), TPS-1901500EU(19V 1.5A), TPS-2001800EU(20V 1.8A), TPS-2401500EU(24V 1.5A)</b></p> <p>Rated Output Power: 36W Max. Output Voltage &amp; Current : 5Vdc-24Vdc, 0.01A-5A AC plug: <b>EU 2pin plug</b> Dimension : 93.5*46*34.1 (mm) Certification: <b>CE,ROHS</b> Efficiency: Level V Input Voltage: 100-240Vac Variation Range: 90-264Vac Load Regulation: <math>V_{out} \pm V_{out} * 5\%</math> Ripple And Noise(Max.): no more than 120mVp-p Turn On Delay Time: 3 second Max. At 230VAC Rise Time: 100mS Max. At 230Vac Hold Up Time: 7mS Min. At 230Vac Protection: OTP/OCP/OVP/SCP Operating Temperature: 0°C to 40°C, Full load, Normal Storage Temperature: -20°C to 85°C Relative Humidity: 5%(0°C)~90%(40°C)RH,72Hrs, Full load, Normal operating Vibration: Operating: IEC 721-3-3 3M3/IEC 721-3-2 2M2/Axes,10 cycles per axis/Dropping tests: 1 corner,3 edges, and 6 surfaces one time for each surface (DIELECTRIC STRENGTH)(Hi-Pot): (Primary to secondary),3000Vac/10mA/1Min. Surge immunity with 1K voltage</p>	

### Remark:

- 1 The DC cable length can be 1.2m, 1.5m, 1.8m, 2.0m, 2.5m, 3.0m.
- 2 DC plug size can be 5.5\*2.1\*10 or 5.5\*2.5\*10 (mm).
- 3 Price will be calculated based on your specific details requirements.
- 4 Payment terms: 30% T/T as deposit,70% T/T before loading!
- 5 Lead time: 35-40days after get the deposit!