

### General Description


These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

BVDSS	RDSON	ID
-60V	190mΩ	-2A

### Features

- -60V,-2A,  $RDS(ON) = 190m\Omega @ VGS = -10V$
- Improved dv/dt capability
- Fast switching
- Green Device Available

### SOT23-3S Pin Configuration



### Applications

- Motor Drive
- Power Tools
- LED Lighting

### Absolute Maximum Ratings $T_c=25^\circ C$ unless otherwise noted

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	-60	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current – Continuous ( $T_A=25^\circ C$ )	-2	A
	Drain Current – Continuous ( $T_A=70^\circ C$ )	-1.6	A
$I_{DM}$	Drain Current – Pulsed <sup>1</sup>	-8	A
$P_D$	Power Dissipation ( $T_A=25^\circ C$ )	1.56	W
	Power Dissipation – Derate above 25°C	0.012	W/°C
$T_{STG}$	Storage Temperature Range	-55 to 150	°C
$T_J$	Operating Junction Temperature Range	-55 to 150	°C

### Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	80	°C/W

**Electrical Characteristics ( $T_J=25\text{ }^{\circ}\text{C}$ , unless otherwise noted)**
**Off Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0\text{V}$ , $I_D=-250\mu\text{A}$	-60	---	---	V
$\Delta BV_{DSS}/\Delta T_J$	$BV_{DSS}$ Temperature Coefficient	Reference to $25\text{ }^{\circ}\text{C}$ , $I_D=-1\text{mA}$	---	-0.05	---	$\text{V}/\text{ }^{\circ}\text{C}$
$I_{DSS}$	Drain-Source Leakage Current	$V_{DS}=-60\text{V}$ , $V_{GS}=0\text{V}$ , $T_J=25\text{ }^{\circ}\text{C}$	---	---	-1	$\mu\text{A}$
		$V_{DS}=-48\text{V}$ , $V_{GS}=0\text{V}$ , $T_J=125\text{ }^{\circ}\text{C}$	---	---	-10	$\mu\text{A}$
$I_{GSS}$	Gate-Source Leakage Current	$V_{GS}=\pm 20\text{V}$ , $V_{DS}=0\text{V}$	---	---	$\pm 100$	nA

**On Characteristics**

$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=-10\text{V}$ , $I_D=-2\text{A}$	---	160	190	$\text{m}\Omega$
		$V_{GS}=-4.5\text{V}$ , $I_D=-1.5\text{A}$	---	200	240	$\text{m}\Omega$
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{GS}=V_{DS}$ , $I_D=-250\mu\text{A}$	-1.2	-1.9	-2.5	V
$\Delta V_{GS(\text{th})}$	$V_{GS(\text{th})}$ Temperature Coefficient		---	5	---	$\text{mV}/\text{ }^{\circ}\text{C}$
$g_{fs}$	Forward Transconductance	$V_{DS}=-10\text{V}$ , $I_D=-2\text{A}$	---	3.5	---	S

**Dynamic and switching Characteristics**







$Q_g$	Total Gate Charge <sup>2, 3</sup>	$V_{DS}=-30\text{V}$ , $V_{GS}=-10\text{V}$ , $I_D=-2\text{A}$	---	8.2	12	nC
$Q_{gs}$	Gate-Source Charge <sup>2, 3</sup>		---	1.8	3.6	
$Q_{gd}$	Gate-Drain Charge <sup>2, 3</sup>		---	1.5	3	
$T_{d(on)}$	Turn-On Delay Time <sup>2, 3</sup>	$V_{DD}=-30\text{V}$ , $V_{GS}=-10\text{V}$ , $R_G=6\Omega$	---	5.2	10	ns
$T_r$	Rise Time <sup>2, 3</sup>		---	19	36	
$T_{d(off)}$	Turn-Off Delay Time <sup>2, 3</sup>		---	35	67	
$T_f$	Fall Time <sup>2, 3</sup>		---	10.6	20	
$C_{iss}$	Input Capacitance	$V_{DS}=-30\text{V}$ , $V_{GS}=0\text{V}$ , $f=1\text{MHz}$	---	425	615	pF
$C_{oss}$	Output Capacitance		---	35	50	
$C_{rss}$	Reverse Transfer Capacitance		---	20	30	
$R_g$	Gate resistance	$V_{GS}=0\text{V}$ , $V_{DS}=0\text{V}$ , $f=1\text{MHz}$	---	17	---	$\Omega$



**Drain-Source Diode Characteristics and Maximum Ratings**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$I_s$	Continuous Source Current	$V_G=V_D=0\text{V}$ , Force Current	---	---	-2	A
$I_{SM}$	Pulsed Source Current		---	---	-4	A
$V_{SD}$	Diode Forward Voltage	$V_{GS}=0\text{V}$ , $I_s=-1\text{A}$ , $T_J=25\text{ }^{\circ}\text{C}$	---	---	-1	V


Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed , pulse width  $\leq 300\text{us}$  , duty cycle  $\leq 2\%$ .
3. Essentially independent of operating temperature.


**Fig.1 Continuous Drain Current vs. TC**

**Fig.2 Normalized RDSON vs. TJ**

**Fig.3 Normalized Vth vs. TJ**

**Fig.4 Gate Charge Waveform**

**Fig.5 Normalized Transient Impedance**

**Fig.6 Maximum Safe Operation Area**


**Fig.7 Switching Time Waveform**

**Fig.8 Gate Charge Waveform**

## SOT23-3S PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.001	0.100	0.000	0.004
b	0.300	0.500	0.012	0.020
c	0.080	0.180	0.003	0.008
D	2.700	3.100	0.106	0.122
E	1.100	1.500	0.043	0.059
E1	2.100	2.640	0.080	0.104
e	0.950 TYP.		0.037 TYP.	
e1	1.780	2.040	0.070	0.080
L	0.550 REF.		0.022 REF.	
L1	0.100	0.500	0.004	0.020
theta	1°	10°	1°	10°