

SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-061108005
ITEM	JPRH 1204-330M Green	版本：D	表單編號：QRRD-01-02

(1) DIMENSION: (UNIT: mm)		DIM.	TOL.
	A	12.5	MAX.
	B	12.5	MAX.
	C	5.0	MAX.
	D	2.8	REF.
	E	7.0	REF.
	F	5.4	REF.
	G		
	H		
	I		
	J		

(2) ELECTRICAL CHARACTERISTIC	TEST INSTRUMENTS.
INDUCTANCE	$33 \pm 20\%$ μ H
TEST FREQUENCY	100 KHz
TEST VOLT	0.1 V
RDC	97 (max) m Ω
IDC	2.7 (max) A




AGILENT 4294A Precision Impedance Analyzer.
 AGILENT 4285A Precision L.C.R. Meter.
 HP-4286A RF L.C.R. Meter.
 ZENTECH 3302 Automatic Components Analyzer.
 ZENTECH 101 L.C.R. Meter.
 WAYNE KERR 6420 Precision Impedance Analyzer.
 ZENTECH 1320 BIAS CURRENT.
 ZENTECH 502AC Resistance Merter.
 ADEX AX-1155B DC Low Ohm Meter.

REMARK :

1. Inductance drop = 25% typ at IDC.
2. $\Delta T = 40^{\circ}C$ rise typ at IDC.

PURCHASER CONFIRMED	APPROVED	CHECKED	DRAWN

SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL	SPEC NO.	SP-061108005	
ITEM	JPRH 1204-330M <input type="checkbox"/> Green	版本：D	表單編號：QRRD-01-02	
(3) Material List				
NO	ITEM	MATERIAL	NOTE	
1	CORE	DR 9.9*4.1 & RI 12.1*4.0*10.65 Or other's equivalent		
2	BASE	C1100		
3	WIRE	SFBW Or other's equivalent	155°C CLASS	
4	SOLDER	100H Or other's equivalent		
5	EPOXY	6020H-6-9(NH) / S-9001A-6B Or other's equivalent		
6	INK	SMD-48A Or other's equivalent	Black	
7	TAPE	MYLAR TAPE	Yellow	
REMARK :				
PURCHASER CONFIRMED :		APPROVED	CHECKED	DRAWN
				

JANTEK

TEL : 886-2-2689-4971 FAX : 886-2-2689-4260

E-mail : jantek@jantek-elec.com.tw

Web-Site : www.jantek-elec.com.tw