


# OA2547AP IP Rated Series



AC Fans - 115, 230V  
254mm x 89mm (10" x 3.5")



<b>Frame</b>	Die Cast Aluminum, Black	<b>Operating Temperature</b> -30°C ~ +80°C  <b>Storage Temperature</b> -40°C ~ +100°C  <b>Life Expectancy</b> 50,000 Hours (L10 at 55°C)  <b>Available Options</b> Tachometer Output Alarm Output Other Speeds  <b>Weight:</b> 5.6 lbs	
<b>Impeller</b>	Steel, 7 Blades		
<b>Connection</b>	Lead Wires, 18 AWG, or Terminals		
<b>Motor</b>	AC, Capacitor Induction, Outer Rotor, Single Phase, Thermally Protected, IP Rated		
<b>Bearing System</b>	Ball Bearings		
<b>Dielectric Strength</b>	1500VAC/min, <5mA		
<b>Insulation Resistance</b>	≥10MΩ @ 500 VDC		

Part Number	Rated Voltage (Volts AC)	Voltage Range (Volts AC)	Input Power (Watts)	Frequency (Hertz)	Rated Speed (RPM)	Max Airflow (CFM)	Noise Level (dBA)	Max Static Pressure ("H <sub>2</sub> O)
OA2547AP-11-1*B18xxx	115	100 ~ 130	95 / 105	50 / 60	2775 / 3250	830 / 1000	70	0.78 / 0.60
OA2547AP-22-1*B18xxx	230	200 ~ 255	95 / 105	50 / 60	2775 / 3250	830 / 1000	70	0.78 / 0.60

\*Insert "T" for Terminals, or "W" for Lead Wires  
xxx Insert "68" for IP68 Rating, or "69K" for IP69K Rating