



BAX-R2U0

2U Rackmount Chassis

- > 2U Rackmount
- > Up to 12"(W) x 9.6"(D) ATX compliant MB
- > 6 x 3.5" Drive Bay or 2 x 5.25" + 4 x 3.5" Drive Bay
- > 7 x Low profile expansion slots
- > 500W PS2 100-240Vac Power Supply
- > Dimension 504 x 482.6 x 88.9 mm
- > Net weight: 7.18kg(Chassis only)

+ Spec

-System Information-	
Processor	Depend on MB
Platform Controller Hub	Depend on MB
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./min. 1sec. or 1min. step
H/W Status Monitor	CPU temperature monitoring Voltages monitoring CPU fan speed control
SBC	ATX MB
-Front I/O-	
USB Port	2 x USB 2.0
Power Button	System power on/off
Reset Button	System reset
LED Indicator	Power status, HDD, LAN activity LEDs
Expansion	
Expansion	7 x Low profile expansion slots
Storage	
Storage	6 x 3.5" Drive Bay or 2 x 5.25" + 4 x 3.5" Drive Bay
Power Requirement	
Adapter	500W PS2 100-240Vac Power Supply
Mechanical & Environmental	
Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
Storage Temperature	-30°C ~ 70°C (-22°F ~ 158°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	504 x 482.6 x 88.9 mm
Construction	Metal
Ordering Information	
Ordering Information	BCC-CASE-R2U0-01R 2U Rackmount Chassis(without 500W PSU) ACC-PSU-500N-01R Power Supply ATX 500W