

4125MVS6WH

Industrial Switched Interlocked Socket Outlet

2CMA162792R1000



Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 6h, rated current 125A, IP67 watertight, 3-poles+neutral+earth

GENERAL

Product Name	Industrial Switched Interlocked Socket Outlet
Product ID	2CMA162792R1000
Function	Switched Interlocked Socket outlet, vertical, Heavy Duty
EAN	7392696627924
Catalog Description	Switched interlocked socket-outlet, vertical, 6h, 125A, IP67, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2420300
E-Number Norway	2416996
E-Number Sweden	E2416996
Standards	IEC 60309-1, -2, -4
RoHS Status	Following EU Directive 2011/65/EU

DIMENSIONS

Product Net Width	175 millimetre
Product Net Height	241 millimetre
Product Net Length	463 millimetre
Product Net Depth	463 millimetre
Product Net Weight	4.3 kilogram

TECHNICAL

Product Main Type	CMVS
Color	Red
Number of Poles	5
Clock Position	6Hour
Rated Current	125 ampere
Rated Voltage	200/346 ... 240/415 volt
Frequency	50 hertz 60 hertz
Degree of Protection	IP67 IP69
Cable Cross-Section	16...70 mm ²
Housing Material	Thermoplastic (PBT)
Plug Angle	
Product Group	Critical&Safe

PACKAGING

Package Width	260 millimetre
Package Height	490 millimetre
Package Gross Weight	4.3 kilogram
Package Length	180 millimetre
Package Units	box 1 piece