



- SPECIFICATIONS**
- Voltage Rating : 125V AC/DC
 - Current Rating : 3A AC/DC
 - Withstanding Voltage : 1,500V AC/minute
 - Insulation Resistance : 1,000M Ω min
 - Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
 - Contact Resistance : 20m Ω max

■ HOUSING

- Part No. : JS-5001-XXX
- JS-5001-XX : GP Produces
- JS-5001-0XX : Non GP Produces
- Poles : 2-14
- Material : Nylon 66 UL94V-2
- Q'ty : 1,000 pcs./Bag

Poles	Part No.	Dimensions(mm)	
		A	B
2	JS-5001-02	3.96	8.92
3	JS-5001-03	7.92	12.88
4	JS-5001-04	11.88	16.84
5	JS-5001-05	15.84	20.80
6	JS-5001-06	19.80	24.76
7	JS-5001-07	23.76	28.72
8	JS-5001-08	27.72	32.68
9	JS-5001-09	31.68	36.64
10	JS-5001-10	35.64	40.60
11	JS-5001-11	39.60	44.56
12	JS-5001-12	43.56	48.52
13	JS-5001-13	47.52	52.48
14	JS-5001-14	51.48	56.44



喬訊電子工業股份有限公司
CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-5001-XX
3.96mm Crimp Style Connectors Housing

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE
林陳鏗	3:1	mm	.0 ±0.3			
CHECKED BY	PROJ	VER NO.	.000 ±0.2			
林勇生		Q1	ALL ±0.1			
DRAWN BY	DATE	SIZE	ANGLE			
徐秀麗	2005/05/15	A4	0° ±			