



REV	EC.N NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	2016.11.24

NOTES:

- Rating: <UL> 300V/10A  
<IEC> 250V/10.5A
- Poles:03P
- Insulation Withstands Voltage: AC2000V/1 Min
- Insulation Resistance: 500MΩ at DC500V
- Using Temperature Range: -40°C/+115°C
- Max soldering : +250° for 5S
- RoHS Compliance.
- Suitable Electric Wire:28-18AWG(UL) 0.2-1.0mm<sup>2</sup> (IEC)
- With" ★ "is important dimension

How to order  
**UL0-TB12 - 250A/3.5 - 08P -1 0 0 0A**

Certificate Factory poles color: Customer requirements  
 Series NO. Code 1:Grey 2:Blue 3:Black 4:Green 5:Orange 6:Red 7:transparent 8:Yellow 9:White

ITEM	NAME OF PART	NO OF PART	Q'TY	MATERIAL	NOTE
5	SHORT-PIN	300TB0020	1	Phosphor bronze	Tin Plated
4	LONG-PIN	300TB0010	2	Phosphor bronze	Tin Plated
3	LEVER	300DD0Y00A	3	PA66	UL94V-0
2	Cover	300TC0Y00A	1	PA66	UL94V-0
1	Housing	300TA0YXXA	3	PA66	UL94V-0

ITEM	NAME OF PART	NO OF PART	Q'TY	MATERIAL	NOTE
DWG	ZCP	16.11.24		MM	SHEET/OF 1/1
CHK	DATE			SCALE	1:1 A4
APP.	DATE			NAME	UL0-TB12-250A/3.5-08P-1000A

NINGBO UL0 ELECTRONICS CO.,LTD.

REV:1.0

2

DWGNO

UL0TB12VMMMA