



| SIZE | STUD SIZE | | B _{+0.1} | L _{+0.2} | F _{+0.2} | H _{+0.1} | ØD _{+0.2} | d _{-0.05} | | | |
|------|-----------|-----|-------------------|-------------------|-------------------|-------------------|--------------------|--------------------|--|--|--|
| | #8 | 4.3 | | | | | | | | | |
| | #8 | 4.3 | 6.6 | 19.6 | 6.3 | 10.0 | 4.2 | 0.7 | | | |

| | Unit | MM (IN) | NO | Technical Requirement | Version | | |
|--------------------|---------------|---------------------------|-----------------------|------------------------------------|---------|-------|----|
| Wire Range | 22-16A.W.G | (0.5-1.5mm ²) | 1 | No oxidation | 4 | | |
| Voltage | 600VOLTS MAX. | | 2 | No structure deformation | 5 | | |
| Current | 19A | | 3 | | 6 | | |
| Part No. | RVS1.25-4 | Terminal material | Brass with tin plated | Made | 高迪 | Check | 杨涛 |
| Drawing No | KT-0612541 | Insulation material | PVC | | | | |
| Date | 2016. 7. 12 | Color | | 浙江珠城科技股份有限公司 | | | |
| Material Thickness | 0.7mm | | | Zhejiang ZUCH Technology CO., Ltd. | | | |