



EMS-CDV-4COM Isolation

Intel® Atom™ Processor D2550 Fanless Rugged Embedded System with 4 COM Isolations



- > Onboard Intel® Atom™ D2550 BGA Processor
- > Intel® NM10 Express Chipset
- > One 204-pin SODIMM Socket Up to 4GB DDR3 1066MHz SDRAM
- > Rich I/O, 1 VGA, 1 LAN, 1 SIM Card Slot, 1 Swappable HDD, 1 Mic-In, 1 Line-In, 1 Line-Out, 1 12-bit GPIO, 1 SMBUS, 6 COM, 2 PS/2 for KB & MS, 2 Knockouts Antenna Mounting, 5 USB
- > Supports 2.5kv Isolation Protection
- > Expansion Slot Supports 2 Mini PCIe Slot
- > Rugged Design for Vibration & Shock Protection
- > Fanless Operating from -10 ~ 60°C
- > Wide Range DC Power Input from 12 ~ 26V
- > Service Window, Easy to Install mSATA, Memory and Mini PCIe Module

+ Spec

System	
Processor	Intel® Atom™ D2550 2-Core 1.86GHz processor
System Chipset	Intel® NM10 Express Chipset
System Memory	1 x 204-Pin DDR3 1066MHz SO-DIMM up to 4 GB
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor Board	Monitoring System Temperature and Voltage with Auto Throttling Control EBM-CDVS + AUX-M07
Expansion	
Expansion	2 x Mini PCIe
Storage	
Storage	1 x 2.5" Drive Bay 1 x mSATA
I/O	
USB	5 x USB 2.0
COM Port	6 x RS-232/422/485 (BIOS)
Other	1 x SIM Card Slot 1 x SMBus 2 x PS2/ KB & MS 2 x Knockouts for Antenna Mounting
DIO	1 x 12bit GPIO
Display	
Chipset	Intel® Cedarview Integrated Graphics
Resolution	VGA:Max. resolution 1920x1200@ 60Hz
Audio	
Chipset	Realtek ALC892
Audio Interface	Mic-In, Line-In and Line-Out
Ethernet	
Chipset	1 x Intel® 82574L
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	1 x RJ-45
Mechanical & Environmental	
Operating Temp	(w/SSD, mSATA), ambient w/ air flow -10°C ~ 60°C (14°F ~ 140°F) (w/HDD), ambient w/ air flow 0°C ~ 45°C (32°F ~ 113°F)
Storage Temp	-40°C ~ 75°C (-40°F ~ 167°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Construction	Aluminum + Metal + Plastic
Mounting Kit	Wall Mount kit (Standard) VESA Mount kit (Optional)
Dimension (L x W x H)	9.45" x 6.69" x 2.36" (240mm x 170mm x 60mm)
Vibration Test	With SSD/mSATA : 5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
Shock Test	With SSD/mSATA : 50Grms, IEC 60068-2-27, Half Sine, 11ms
Certifications	
Certification Information	CE FCC Class B
Software Support	
OS Information	Win XP Win 7 Linux
Power Requirement	



Power Connector	Lockable DC Jack
Power Requirement	+12V ~ +26V TVS component for surge protection
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 3.0 Compliant
Power Mode	AT/ATX (ATX is default setting)
Adapter	Input: 100 ~ 240Vdc/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter

Ordering

EMS-CDV-255-A1-4R
Intel® Atom™ Processor D2550 Fanless Rugged Embedded System with 4 COM Isolations