



FILE: 2016-D02\ULO

REV	E.C.N NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	2016.12.20

- NOTES:
- Rating: <UL> 300V/10A  
<IEC> 250V/10.5A
  - Poles:02-24P
  - Insulation Withstands Voltage: AC2000V/1 Min
  - Contact resistance: 20mΩ
  - Screw Torque Vlaue:0.2Nm
  - Insulation Resistance: 500MΩ at DC500V
  - Wire range: 1.5mm<sup>2</sup> (IEC), 16-28AWG(UL);
  - Using Temperature Range: -40°C/+115°C
  - RoHS Compliance.
  - With "★" is important dimension

How to order  
**ULO-TB15 - 15KAM/3.81 - □□P -Y 0 0 0A**

Certificate Series NO.      Factory Code      poles      color:      Customer requirements

1:Grey  
 2:Blue  
 3:Black  
 4:Green  
 5:Orange  
 6:Red  
 7:transparent  
 8:Yellow  
 9:White

6	Screw	S000000170	2	Steel	Zn plated
5	Screw	S000000140	N	Steel	Zn plated
4	Cage	X000000110	N	Brass	Ni Plated
3	Clamp	1013B0010	N	Phosphor Bronze	Sn Plated
2	Cover	1013C0YXXA	1	PA66	UL94V-0
1	HOUSING	1015A0YXXA	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCP	DATE	16.12.20	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
				NAME	<b>ULO-TB15-15KAM/3.81-XXP-Y000A</b>
				DWGNO.	ULOTB15Y000A

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	—	//		
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	all	over 0	over 100	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5		