

# eBOX640-500-FL NEW

Fanless Embedded System with LGA1151 Socket 6th/7th Gen Intel® Core™ & Celeron® Processor, Intel® H110, 1 HDMI/DP/VGA, 4 USB 3.0, 4 COM, 1 Mini PCI and 10 ~ 30 VDC

## Features

- LGA1151 socket 6th/7th gen Intel® Core™ i7/i5/i3 & Celeron® processor (Skylake/Kabylake)
- Fanless operation with compact size design
- 4 COM, 6 USB and 2 GbE LANs
- Two 2.5" SATA drive bay, 1 PCI Express Mini Card slot and 1 SIM slot
- Front panel I/O connectivity design
- 10 ~ 30 VDC wide range power input




## Specifications

Standard Color	Silver-Black
Construction	Aluminum extrusion and heavy-duty steel, IP40
CPU	6th/7th Gen Intel® Core™ i7/i5/i3 & Celeron® processor (CPU TDP max. up to 35W)
System Memory	2 x 288-pin DDR4-2133 DIMM, up to 32GB
Chipset	Intel® H110
BIOS	AMI
System I/O Outlet	1 x RS-232/422/485 3 x RS-232 2 x 10/100/1000Mbps Ethernet (Intel® i219LM & i211AT) 2 x USB 2.0 4 x USB 3.0 1 x Audio (Mic-in/Line-out) 1 x DisplayPort 1 x HDMI 1 x VGA 1 x 10 ~ 30 VDC power input connector 1 x AT/ATX quick switch 2 x SMA type connector opening for antenna 1 x ATX power switch
Watchdog Timer	255 levels, 1 ~ 255 sec.
Storage	2 x 2.5" SATA HDD bay 1 x mSATA
Expansion Interface	1x full-size PCI Express Mini Card slot with mSATA supported (PCI Express + USB signal) 1 x SIM slot
System Indicator	1 x green for system power 1 x orange LED for HDD active
Power Supply	10 ~ 30 VDC
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F) (with W.T. DRAM & SSD)
Humidity	10% ~ 90%, non-condensing
Vibration Endurance	2 Grms with SSD (5 ~ 500 Hz, X, Y, Z directions)
Dimensions	182 mm (7.16") (W) x 230 mm (9.05") (D) x 82 mm (3.23") (H)
Weight (net/gross)	3 kg (6.61 lb)/3.6 kg (7.94 lb)
Certificate	CE, FCC Part 15B Class A
EOS support	Win10 IoT, WE8S

## Packing List

- 1 x Quick manual
- 1 x Driver CD
- 1 x Screw pack
- 4 x Foot pad
- 1 x 3-pin terminal block connector



## Power Protection

### DC Version

- OCP (over current protection)
- UVP (under voltage protection)

## Ordering Information

### Standard

eBOX640-500-FL-DC	Fanless Embedded System with LGA1151 6th/7th gen Intel® Core™ i7/i5/i3 & Celeron® processor, Intel® H110, 1 HDMI/DP/VGA, 4 USB 3.0, 4 COM, 1 PCI Express Mini Card slot and 10 ~ 30 VDC
-------------------	---

### Optional

2.5" SATA HDD	80GB or above
2.5" SATA SSD	40GB or above
DDR4 RAM	2GB ~ 16GB
mSATA	512MB or above
Wall mount kit	8816K6400A0E
DIN-rail kit	8816K6401A0E
Wi-Fi module	
3G/LTE module	
24V 12W adapter	50966D45000E

\*Specifications and certifications may vary according to various options.

## Dimensions

